

Design By	
Ernesto Gismondi	

Collection

Design

ED	շ(Մը) us	(IP20)	(

Specifications	
Delivered lumens	2857.48lm
Light output ratio	71.44lm/W
Power consumption	41W
Led type	35W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire / Dimmable 0-10V
Input Voltage	120-277V
Driver	EFORE - 1 x RCL050-1050A

Colors & Finishes —

Transparent (Diffuser)

Black (Rim,Canopy,Cable)

Materials =

- Rounded rim in ultra-light aluminum
- Diffuser in clear PMMA

Features & Accessories

- Rim hosts a LED strip injecting light into a clear surface
- Diffuser is transparent when off, filled with light when on
- The dimming range of the driver can dim down to 1%
- Driver is compatible to both 2-wire dimming and 0-10V dimming options

Dimensions =



Packaging =

Boxes

Lig		

Direct

Luminaire weight —

N/A

Warranty





Design By	
Ernesto Gismondi	

Collection -

Design

	ը Մի	(P20)	(
4		\sim	





Colors & Finishes —

Transparent (Diffuser) Polished Aluminum (Canopy & Rim)

Materials =

- Rounded rim in ultra-light aluminum
- Diffuser in clear PMMA


Specifications —

Delivered lumens	2857.48lm
Light output ratio	71.44lm/W
Power consumption	41W
Led type	35W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire / Dimmable 0-10V
Input Voltage	120-277V
Driver	EFORE - 1 x RCL050-1050A

Features & Accessories =

- Rim hosts a LED strip injecting light into a clear surface
- Diffuser is transparent when off, filled with light when on
- The dimming range of the driver can dim down to 1%
- Driver is compatible to both 2-wire dimming and 0-10V dimming options

Dimensions =



Packaging =

2 Boxes

1 x 45-3/8" x 36-11/16" x 3-5/8" / 16.8 lbs - 115 cm x 93 cm x 9 cm / 7.62 kg

Light distribution -

Direct

Luminaire weight =

16.76 lbs / 7.6 kg

Warranty =



1993038A-EXT



Design By =

Ernesto Gismondi

Collection =

Design



(1) (1) (2) (2) (1) (1)

Colors & Finishes —

Transparent (Diffuser) Black (Rim,Canopy,Cable)

Materials =

- Rounded rim in ultra-light aluminum
- Diffuser in clear PMMA


Specifications —

Delivered lumens	4859.31lm
Light output ratio	80.99lm/W
Power consumption	62W
Led type	56W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire / Dimmable 0-10V
Input Voltage	120-277V
Driver	EFORE - x RCL040-0800A

Features & Accessories =

- Rim hosts a LED strip injecting light into a clear surface
- Diffuser is transparent when off, filled with light when on
- The dimming range of the driver can dim down to 1%
- Driver is compatible to both 2-wire dimming and 0-10V dimming options

Dimensions =



Packaging =

1 x 46-15/16" x 5-3/8" x 44-9/16" / 22.8 lbs - 119 cm x 13.5 cm x 113 cm / 10.34 kg

Light distribution =

Direct

Luminaire weight =

14.68 lbs / 6.66 kg

Warranty =

5 year limited warranty





_				_	
1)€	124	a	n	В١	1

Ernesto Gismondi

Collection =

Design



Colors & Finishes

Transparent (Diffuser)

Polished Aluminum (Canopy & Rim)

(W) # (P20)

Materials =

- Rounded rim in ultra-light aluminum
- Diffuser in clear PMMA


Specifications —

Delivered lumens	4859.31lm
Light output ratio	80.99lm/W
Power consumption	62W
Led type	56W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire / Dimmable 0-10V
Input Voltage	120-277V
Driver	EFORE - 2 x RCL040-0800A

Features & Accessories

- Rim hosts a LED strip injecting light into a clear surface
- Diffuser is transparent when off, filled with light when on
- The dimming range of the driver can dim down to 1%
- Driver is compatible to both 2-wire dimming and 0-10V dimming options

Dimensions =



Packaging =

2 Boxes

1 x 46-15/16" x 5-3/8" x 44-9/16" / 22.8 lbs - 119 cm x 13.5 cm x 113 cm / 10.34 kg

Light distribution =

Direct

Luminaire weight

29.36 lbs / 13.32 kg

Warranty



Design By	
Design by	
Ernesto Gismondi	

Collection =

Design



Colors & Finishes -

Transparent (Diffuser) Black (Rim,Canopy,Cable)

Materials =

- Rounded rim in ultra-light aluminum
- Diffuser in clear PMMA

Specifications —

Delivered lumens	6761.93lm
Light output ratio	84.52lm/W
Power consumption	83W
Led type	71W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire / Dimmable 0-10V
Input Voltage	120-277V
Driver	EFORE - 2 x RCL050-1050A

Features & Accessories =

- Rim hosts a LED strip injecting light into a clear surface
- Diffuser is transparent when off, filled with light when on
- The dimming range of the driver can dim down to 1%
- Driver is compatible to both 2-wire dimming and 0-10V dimming options

Dimensions =

Extended length Min 70⁷⁸"- Max 230" Min 180 cm - Max 548 cm

Light distribution

Direct

Luminaire weight =

N/A

Warranty =

5 year limited warranty



Boxes





Ernesto Gismondi

Collection =

Design



(1) (1) (2) (2) (1) (1)

Colors & Finishes =

	Transparent (Diffuser)
A	Bronze (Rim & Canopy)

Materials =

- Rounded rim in ultra-light aluminum
- Diffuser in clear PMMA


Specifications —

Delivered lumens	6761.93lm
Light output ratio	84.52lm/W
Power consumption	83W
Led type	71W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire / Dimmable 0-10V
Input Voltage	120-277V
Driver	N/A

Features & Accessories =

- Rim hosts a LED strip injecting light into a clear surface
- Diffuser is transparent when off, filled with light when on
- The dimming range of the driver can dim down to 1%
- Driver is compatible to both 2-wire dimming and 0-10V dimming options

Dimensions =



Light distribution =

Direct

Luminaire weight =

23.15 lbs / 10.5 kg

Warranty =

5 year limited warranty



1 x 62-11/16" x 62-11/16" x 5-13/16" / 40.12 lbs - 159 cm x 159 cm x 14.5 cm / 18.2 kg





Design By —	

Ernesto Gismondi

Collection =

Design



Colors & Finishes -

Transparent (Diffuser) Polished Aluminum (Canopy & Rim)

Materials =

- Rounded rim in ultra-light aluminum
- Diffuser in clear PMMA


Specifications —

Delivered lumens	6761.93lm
Light output ratio	84.52lm/W
Power consumption	83W
Led type	71W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire / Dimmable 0-10V
Input Voltage	120-277V
Driver	EFORE - 2 x RCL050-1050A

Features & Accessories =

- Rim hosts a LED strip injecting light into a clear surface
- Diffuser is transparent when off, filled with light when on
- The dimming range of the driver can dim down to 1%
- Driver is compatible to both 2-wire dimming and 0-10V dimming options

Dimensions =



Light distribution =

Direct

Luminaire weight =

47 lbs / 21.32 kg

Warranty =

Packaging =

2 Boxes

1 x 62-11/16" x 62-11/16" x 5-13/16" / 40.48 lbs - 159 cm x 159 cm x 14.5 cm / 18.36 kg

