

# Discovery wall/ceiling Polished Aluminum

1998018A

## SPECIFICATIONS



### Design By

Ernesto Gismondi

### Collection

Design



### Specifications

Delivered lumens	2474.65lm
Light output ratio	49.49lm/W
Power consumption	49.3W
Led type	39W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire
Input Voltage	120V
Driver	HATCH - 1 x LC40-2100P-120-G

### Colors & Finishes

- ☐ Transparent (Diffuser)
- ☒ Polished Aluminum (Rim & Backplate)


### Materials

- Rounded rim in ultra-light aluminum
- Diffuser in clear PMMA

### Features & Accessories

- Rim hosts a LED strip injecting light into a clear surface
- Diffuser is transparent when off, filled with light when on

### Dimensions



### Packaging

1 Box

1 x 47-5/16" x 40-5/8" x 4-7/16" / 16.53 lbs - 120 cm x 103 cm x 11 cm / 7.5 kg

### Light distribution

Direct/Indirect

### Luminaire weight

7.72 lbs / 3.5 kg


### Warranty

5 year limited warranty

# Discovery ADA wall/ceiling Black

1998038A

## SPECIFICATIONS



### Design By

Ernesto Gismondi

### Collection

Design



### Specifications

Delivered lumens	2474.65lm
Light output ratio	49.49lm/W
Power consumption	49.3W
Led type	39W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire
Input Voltage	120V
Driver	HATCH - 1 x LC40-2100P-120-G

### Colors & Finishes

- ☐ Transparent (Diffuser)
- ☒ Black (Rim & Backplate)


### Materials

- Rounded rim in ultra-light aluminum
- Diffuser in clear PMMA

### Features & Accessories

- Rim hosts a LED strip injecting light into a clear surface
- Diffuser is transparent when off, filled with light when on

### Dimensions



### Packaging

1 Box

1 x 47-5/16" x 40-5/8" x 4-7/16" / 16.53 lbs - 120 cm x 103 cm x 11 cm / 7.5 kg

### Light distribution

Direct/Indirect

### Luminaire weight


7.72 lbs / 3.5 kg

### Warranty

# Discovery ADA wall/ceiling bronze

1998068A

## SPECIFICATIONS



### Design By

Ernesto Gismondi

### Collection

Design



### Specifications

Delivered lumens	2474.65lm
Light output ratio	49.49lm/W
Power consumption	49.3W
Led type	39W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire
Input Voltage	120V
Driver	N/A

### Colors & Finishes

- ☐ Transparent (Diffuser)
- ☒ Bronze (Rim & Backplate)


### Materials

- Rounded rim in ultra-light aluminum
- Diffuser in clear PMMA

### Features & Accessories

- Rim hosts a LED strip injecting light into a clear surface
- Diffuser is transparent when off, filled with light when on

### Dimensions



### Packaging

1 Box

1 x 47-5/16" x 40-5/8" x 4-7/16" / 16.53 lbs - 120 cm x 103 cm x 11 cm / 7.5 kg

### Light distribution

Direct/Indirect

### Luminaire weight

7.72 lbs / 3.5 kg

### Warranty

5 year limited warranty