

Discovery suspension Polished Aluminum

1999118A

SPECIFICATIONS



Design By

Ernesto Gismondi

Collection

Design



Specifications

Delivered lumens	2835.48lm
Light output ratio	69.1lm/W
Power consumption	41W
Led type	35W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire / Dimmable 0-10V
Input Voltage	120-277V
Driver	EFORE - 1 x RCL050-1050A

Colors & Finishes

- ☐ Transparent (Diffuser)
- ☒ Polished Aluminum (Canopy & Rim)
- ☐ Clear (Feed cable)


Materials

- Rounded rim in ultra-light aluminum
- Diffuser in clear PMMA

Features & Accessories

- Rim hosts a LED strip injecting light into a clear surface
- Diffuser is transparent when off, filled with light when on
- Extended cable length
- Driver is compatible to both 2-wire dimming and 0-10V dimming options

Dimensions



Packaging

1 Box

1 x 45-3/8" x 36-11/16" x 3-5/8" / 17.39 lbs - 115 cm x 93 cm x 9 cm / 7.89 kg

Light distribution

Direct

Luminaire weight

8.11 lbs / 3.68 kg

Warranty

Discovery suspension Black

1999138A

SPECIFICATIONS



Design By

Ernesto Gismondi

Collection

Design



Specifications

Delivered lumens	2835.48lm
Light output ratio	69.1lm/W
Power consumption	41W
Led type	35W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire / Dimmable 0-10V
Input Voltage	120-277V
Driver	EFORE - 1 x RCL050-1050A

Colors & Finishes

- ☐ Transparent (Diffuser)
- ☒ Black (Rim, Canopy, Cable)


Materials

- Rounded rim in ultra-light aluminum
- Diffuser in clear PMMA

Features & Accessories

- Rim hosts a LED strip injecting light into a clear surface
- Diffuser is transparent when off, filled with light when on
- Extended cable length
- Driver is compatible to both 2-wire dimming and 0-10V dimming options

Dimensions



Packaging

1 Box

1 x 36-11/16" x 45-3/8" x 3-5/8" / 17.39 lbs - 93 cm x 115 cm x 9 cm / 7.89 kg

Light distribution

Direct

Luminaire weight

8.11 lbs / 3.68 kg

Warranty

Discovery suspension bronze

1999168A

SPECIFICATIONS



Design By

Ernesto Gismondi

Collection

Design



Specifications

Delivered lumens	2835.48lm
Light output ratio	69.1lm/W
Power consumption	41W
Led type	35W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire / Dimmable 0-10V
Input Voltage	120-277V
Driver	EFORE - x RCL050-1050A

Colors & Finishes

- ☐ Transparent (Diffuser)
- ☒ Bronze (Rim & Canopy)


Materials

- Rounded rim in ultra-light aluminum
- Diffuser in clear PMMA

Features & Accessories

- Rim hosts a LED strip injecting light into a clear surface
- Diffuser is transparent when off, filled with light when on
- Extended cable length
- Driver is compatible to both 2-wire dimming and 0-10V dimming options

Dimensions



Packaging

1 Box

1 x 45-3/8" x 36-11/16" x 3-5/8" / 17.39 lbs - 115 cm x 93 cm x 9 cm / 7.89 kg

Light distribution

Direct

Luminaire weight

8.11 lbs / 3.68 kg

Warranty

5 year limited warranty