

# Obice mini wall 18°

T430418W18

## SPECIFICATIONS



### Design By

Alessandro Pedretti

### Collection

Outdoor



### Colors & Finishes

Black

### Materials

- Body in injection molded aluminum
- Terminal base and adjustable joint in injection molded aluminum
- Diffuser in 1/64" (4mm)-thick tempered glass with black opal serigraphy

### Specifications


Delivered lumens	505lm
Light output ratio	72lm/W
Power consumption	7W
Led type	7W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	On/Off
Input Voltage	24VDC
Driver	Remote power supply (sold separately)
BUG Rating	B1-U0-G0

\*Integrated light source

### Features & Accessories

- Tilting angle +35°/-125°
- Rotation on horizontal axis 359°
- Wiring to be carried out by means of a plug located in the terminal base
- Standard non dimmable
- Transformer 24vDC 60W 120v(EX95121)

### Dimensions




### Packaging

1 Box

1 x 12-11/16" x 12-11/16" x 8-9/16" / 4.33 lbs - 32 cm x 32 cm x 21.5 cm / 1.965 kg

### Light distribution

Direct



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

### Luminaire weight

2.79 lbs / 1.27 kg

### Warranty

5 year limited warranty