Obice wall 34° T430534W18

SPECIFICATIONS



Design By -----

Alessandro Pedretti

Outdoor



Colors & Finishes

Black

Materials =

- Body in injection molded aluminum
- Terminal base and adjustable joint in injection molded aluminum
- Diffuser in 1/64" (4mm)-thick tempered glass with black opal serigraphy

Specifications	
Delivered lumens	605lm
Light output ratio	61lm/W
Power consumption	10W
Led type	8W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	On/Off
Input Voltage	120V
Driver	MEAN WELL - 1 x LPC-20-700
BUG Rating	B1-U0-G0

*Integrated light source

Features & Accessories -

• Tilting angle +35°/-125°

Rotation on horizontal axis 359°


- Wiring to be carried out by means of a plug located in the terminal base
- Standard non dimmable

Dimensions —

Packaging =


1 Box

1 x 12-11/16" x 12-11/16" x 8-9/16" / 5.25 lbs - 32 cm x 32 cm x 21.5 cm / 2.38 kg



Light distribution -


Direct



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane 3.86 lbs / 1.75 kg

Warranty —

5 year limited warranty



We reserve the right to change specifications of our products. For the latest product information please visit www.artemide.net

